



Firma: ISCom d.o.o.
Adresa: T.C. "Danubius" Karađorđeva 12,
lokali 28, 156 i 156a
Telefon: 026/4-100-500, 069/4-100-500
Fax:
PIB: 104927929
E-mail: prodaja@iscom.rs

GMB-500-PRO Gembird napajanje 500W 80+,
PFC,12cm FAN, 20+4pin, 2x4pin, 6+2pin,
4xSATA,2xIDE

Šifra: 30580
Kategorija proizvoda: Napajanja
Proizvođač: GEMBIRD

Cena: **3.990,00** rsd.



Manufacturer : Gembird - Scorpion Series

Model: GMB-500 PRO

Power: 500W 80+, CE/TuV/ ROHS

Format: ATX V2.31 and EPS

- Active PFC

- Energy efficiency 80+ : 82%, 85%, 82% at 20%, 50%, 100% load

- Red color 12cm ball bearing Fan temperature controlled for low-noise performance. MTBF: 100,000 h

- Protection: OVP/ UVP/ OPP/ SCP (Over Voltage Protection, Under Voltage Protection, Over Power Protection, Short Circuit Protection)

- 100% burn-in/vibration/Hi Pot/Leakage current Test.

- Incl. 1.2m EU power cord

- Input socket +I/O

- On/Off Switch

- Cable length: all > 50cm.

Dimension: 150x140x85mm

- Connectors, cables all with BLACK MESH :

1x MB ATX 12V 20+4 Pin (50cm)

1x CPU ATX12V 4+4 Pin (55cm)

1x PCI-E 6+2 (8) Pin (45cm + 15cm)

2x Molex 4 Pin (50molex +15sata +15sata)

4x S-ATA (50molex +15sata +15sata +15sata)

DC-Output:

+12V SINGLE RAIL : nominal 40A (peak 52A) for MB + GPU like AMD Radeon RX5700

+5V : 12A (peak 20A)

+3.3V : 12A (peak 20A)

-12V : 0.3A (peak 0.3A)

+5Vsb : 2A (peak 2A)

Proizvodac: Gembird - Scorpion Series

Model: GMB-500 PRO

Snaga: 600V 80+, CE / TuV / ROHS

Format: ATX V2.31 i EPS

- Aktivni PFC

- Energetska efikasnost 80+ : 82%, 85%, 82% pri 20%, 50%, 100% opterećenja

- Ventilator sa kuglicnim ležajem crvene boje od 12cm, za performanse sa niskom bukom. MTBF: 100.000h

- Zaštita: OVP / UVP / OPP / SCP (Zaštita od prenapona, Podnaponska zaštita, Zaštita od prekomerne struje, zaštita od kratkog spoja)

- 100% izgaranje / vibracije / Hi Pot / Test curenja struje.

- Pakovanje sadrži EU kabl za napajanje od 1,2m

- Ulazna uticnica + I / O

- Prekidac za ukljucivanje / iskljucivanje

- Dužina kabla: sve > 50cm.

Dimenzije: 150x140x85mm

- Konektori, kablovi sa CRNIM MREŽAMA:

1x MB ATX 12V 20+4 Pin (50cm)

1x CPU ATX12V 4+4 Pin (55cm)

1x PCI-E 6+2 (8) Pin (45cm + 15cm)

2x Molex 4 Pin (50molex +15sata +15sata)

4x S-ATA (50molex +15sata +15sata +15sata)

DC-izlaz:

+ 12V SINGLE RAIL: nominalno 40A (maksimum 52A) za MB + GPU poput AMD Radeon RX5700

+ 5V: 12A (maksimum 20A)

+ 3.3V: 12A (maksimum 20A)

-12V: 0,3A (maksimum 0,3A)

+ 5Vsb: 2A (maksimum 2A)